



Greenstar CDi Highflow Installer overview

Ultra powerful heating



Ultra powerful heating

When your customers need a powerful and fast-flowing boiler, look no further than the CDi Highflow. It fills a kitchen sink in 19 seconds, with enough in the tank for big 2-bath homes, and it still fits neatly under the worktop.

Why install the Greenstar CDi Highflow?



Guaranteed

10 years peace of mind*



Rapid comfort

Fills the kitchen sink in 19 seconds



Powerful

Plenty in the tank for 2-bath homes



Convenient

Fits under the kitchen counter



SimpleSwitch

From a previous Frost protection included Highflow for simpler installation



Dimensions (h x w x d) 850mm x 600mm x 600mm[^]

Available boiler types

Combi

Technical data		CDi Highflow 440	CDi Highflow 550
ErP space heating efficiency class		A / 92%	A / 92%
ErP hot water efficiency class		В	В
Dimensions	Width	600mm	600mm
	Height	850mm	850mm
	Depth	600mm^	600mm^
Clearances	Above flue	15mm**	15mm**
	Sides	5mm	5mm
	Front	15mm [†]	15mm [†]
Combi flow rate at the hot water tap (35°C)		20l/min#	25/min#
Combi central heating output		7.4kW-29.2kW	9.7kW-30.6kW
Sound power level dB(A)		53	52
Maximum flue length (60/100mm)		4m horizontal & 6.4m vertical	4m horizontal & 6.4m vertical

29kW NG - Part No. 7 731 600 098

Available outputs

41kW NG - Part No. 7 731 600 100 29kW LPG - Part No. 7 731 600 099

41kW LPG - Part No. 7 731 600 101

^Excluding front fascia.
**600mm required for installation.
*600mm required for servicing. Refer to installation and servicing instructions for unventilated clearances.
#Flow rate shown is only until the heat store is depleted. Once this happens, it is advisable to reduce the flow rate to maintain the DHW temperature at the outlet.



For more information, scan the QR code to visit our website.